Page: 1 of 6

This version issued: June, 2023

Phone: +61 3 9028 4265

Section 1 - Identification of the Material and Supplier

ATECH PRODUCTS PTY LTD

LEVEL 1, 457 ELIZABETH ST SURRY HILLS NSW 2010

AUSTRALIA

Chemical nature: Hardener part of two part epoxy system

Trade Name: EPOFLOOR® LEVELLER PART B

Product Use: Multi-purpose epoxy flooring system

Creation Date: May, 2017

This version issued: June, 2023 and is valid for 5 years from this date.

Poisons Information Centre: Phone 13 11 26 from anywhere in Australia

EMERGENCY RESPONSE NUMBER

Organisation: CHEMWATCH EMERGENCY RESPONSE

Emergency response number(s): Australia: +61 3 9573 3188

New Zealand: +64 800 700 112

Other emergency response number(s): +61 1800 951 288

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xn, Harmful. N, Dangerous to the environment. C, Corrosive. Hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: None allocated.

ADG Classification: Class 8: Corrosive Substances.

UN Number: 2735, AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.









Phone: +61 3 9028 4265

GHS Signal word: DANGER

Acute Toxicity Oral Category 4

Acute Toxicity Dermal Category 4

Skin Corrosion Category 1

Skin Sensitisation Category 1

Acute Toxicity Inhalation Category 4

Respiratory Sensitization Category 1

Specific Target Organ Toxicity - Single Exposure Category 3

Hazardous to aquatic environment Short term/Chronic Category 2

HAZARD STATEMENT:

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

PREVENTION

P260: Do not breathe fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

SAFETY DATA SHEET

Issued by: Atech Products Pty Ltd

Page: 2 of 6

This version issued: June, 2023

P264: Wash contacted areas thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves, protective clothing and eye or face protection.

P285: In case of inadequate ventilation wear respiratory protection.

RESPONSE

P310: Immediately call a POISON CENTRE or doctor/physician.

P363: Wash contaminated clothing before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P304+P341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313: If skin irritation or rash occurs: Get medical advice.

P342+P311: If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.

P391: Collect spillage.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam. Water fog or fine spray is the preferred medium for large fires.

STORAGE

P405: Store locked up.

P410: Protect from sunlight.

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: Yellow liquid

Odour: Amine odour

Major Health Hazards: causes burns, harmful by inhalation, in contact with skin, and if swallowed, may cause sensitisation by inhalation and skin contact, vapours may cause drowsiness and dizziness.

Section 3 - Composition/Information on Ingredients				
Ingredients	CAS No	Conc, %	TWA (mg/m³)	STEL (mg/m ³)
Benzyl alcohol	100-51-6	25-50	not set	not set
Isophoronediamine	2855-13-2	10-25	not set	not set
Benzene-1,3-dimethanamine	1477-55-0	10-25	0.1	Peak
Salicylic acid	69-72-7	2.5-10	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: If symptoms of poisoning become evident, contact a Poisons Information Centre, or call a doctor at once. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. DO NOT allow victim to move about unnecessarily. Symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Issued by: Atech Products Pty Ltd Phone: +61 3 9028 4265

Page: 3 of 6

This version issued: June, 2023

Skin Contact: Flush contaminated area with lukewarm, gently flowing water for at least 40 minutes, by the clock. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this MSDS and take their advice). Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts). Strongly basic ingredients tend to penetrate the skin and so need longer rinsing than other substances. If irritation persists, repeat flushing. Seek medical attention.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 20-30 minutes, by the clock, while holding the eyelid(s) open. Neutral saline solution may be used as soon as it is available. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this MSDS and take their advice). Take care not to rinse contaminated water into the unaffected eye or onto face. If irritation persists, repeat flushing. Call a Poisons Information Centre or a doctor urgently. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is little risk of an explosion from this product if commercial quantities are involved in a fire. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures. Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam. Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses. Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is little danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal

Flash point: >100°C
Upper Flammability Limit: 13.0%
Lower Flammability Limit: 1.2%
Autoignition temperature: 380°C

Flammability Class: Not flammable (GHS); C1 combustible (AS 1940)

protective equipment is liquid-tight chemical protective clothing and breathing apparatus.

Section 6 - Accidental Release Measures

Accidental release: As this product is classed as a respiratory sensitiser, special care should be taken with respiratory selection if you are sensitised to this product or any of its declared ingredients. Eye/face protective equipment should comprise, as a minimum, protective glasses and, preferably, goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a suitable cartridge. Consult AS/NZS 1715.Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Because of the corrosiveness of this product, special personal care should be taken in any cleanup operation. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Store in a cool, well ventilated area. Check containers periodically for corrosion and leaks. Containers should be kept closed in order to minimise contamination. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 10000kg or L of Dangerous Goods of Packaging Group III, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Page: 4 of 6

This version issued: June, 2023

Phone: +61 3 9028 4265

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits TWA (mg/m³) STEL (mg/m³)
Benzene-1,3-dimethanamine 0.1 Peak

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems. **Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Your eyes must be completely protected from this product by splash resistant goggles with face shield. All surrounding skin areas must be covered. Emergency eye wash facilities must also be available in an area close to where this product is being used.

Skin Protection: Because of the dangerous nature of this product, make sure that all skin areas are completely covered by impermeable gloves, overalls, hair covering, apron and face shield. See below for suitable material types. **Protective Material Types:** We suggest that protective clothing be made from the following materials: butyl rubber.

Respirator: As this product is classed as a respiratory sensitiser, special care should be taken with respiratory selection if you are sensitised to this product or any of its declared ingredients. If there is a significant chance that vapours or mists are likely to build up in the area where this product is being used, we recommend that you use a respirator. It should be fitted with a suitable cartridge. Consult AS/NZS 1715.Otherwise, not normally necessary. Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour: Yellow liquid
Odour: Amine odour
Boiling Point: >200°C at 100kPa

Freezing/Melting Point: No specific data. Liquid at normal temperatures. **Volatiles:** No specific data. Expected to be low at 100°C.

No data

Vapour Pressure: Negligible. **Vapour Density:** No data. **Specific Gravity:** 1.06 Water Solubility: Immiscible. :Hq No data. Volatility: No data. **Odour Threshold:** No data. **Evaporation Rate:** No data.

Viscosity: 200 cSt at 40°C

Autoignition temp: 380°C

Coeff Oil/water Distribution:

Section 10 - Stability and Reactivity

Reactivity: Most strong alkalis and bases react with inorganic and organic acids to form salts. They can also react with some metals liberating hydrogen gas. These reactions may be rapid and sometimes liberate much heat. They can also decompose many organic materials such as esters, in a reaction called hydrolysis.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Keep containers and surrounding areas well ventilated. Keep isolated from combustible materials. Protect this product from light.

Incompatibilities: acids, oxidising agents, zinc, tin, aluminium and their alloys, acid chlorides, acid anhydrides, chloroformates.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas in reducing atmospheres. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: Polymerisation reactions are unlikely; they are not expected to occur.

Product Name: EPOFLOOR® LEVELLER PART B
Page: 5 of 6

This version issued: June, 2023

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Isophoronediamine is classed by SWA as a potential sensitiser by skin contact.

Classification of Hazardous Ingredients

Ingredient Risk Phrases

Benzyl Alcohol Conc>=25%: Xn; R20/22

• Acute toxicity - category 4

Isophoronediamine >=10%Conc<25%: C; R34; R43

Acute toxicity - category 4Skin corrosion - category 1B

Skin sensitisation - category 1

Hazardous to the aquatic environment (chronic) - category 3

Salicylic Acid >=5%Conc<10%: Xi; R36

Acute toxicity - category 4Eye damage - category 1

Potential Health Effects

Persons sensitised to isophoronediamine should avoid contact with this product.

Inhalation:

Short Term Exposure: High vapour pressures may cause drowsiness and dizziness. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort. If liquid enters nasal passages, it will cause pain and burn nasal membranes. Patients with inhalation burns may develop acute pulmonary oedema.

Long Term Exposure: Vapours may cause drowsiness and dizziness.

Skin Contact:

Short Term Exposure: Available data shows that this product is harmful, but symptoms are not available. In addition product is corrosive to the skin. Capable of causing moderate to severe burns with ulceration. Can penetrate to deeper layers of skin, resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure. Burns may not be immediately painful; the onset of pain may be minutes to hours.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eve Contact:

Short Term Exposure: This product is corrosive to eyes. It will cause severe pain, and corrosion of the eye and surrounding facial tissues. Unless exposure is quickly treated, permanent blindness and facial scarring is likely.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. Available data shows that this product is harmful, but symptoms are not available. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP. **IARC:** No significant ingredient is classified as carcinogenic by IARC.

Section 12 - Ecological Information

Toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment. Insufficient data to be sure of status.

SAFETY DATA SHEET

Issued by: Atech Products Pty Ltd Phone: +61 3 9028 4265

This version issued: June, 2023

Section 13 - Disposal Considerations

Disposal: Special help is available for the disposal of Agricultural Chemicals. The product label will give general advice regarding disposal of small quantities, and how to cleanse containers. However, for help with the collection of unwanted rural chemicals, contact ChemClear 1800 008 182 http://www.chemclear.com.au/ and for help with the disposal of empty drums, contact DrumMuster http://www.drummuster.com.au/ where you will find contact details for your area.

Section 14 - Transport Information

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number: 2735, AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.

Hazchem Code: 2X

Special Provisions: 223, 274

Limited quantities: ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

Dangerous Goods Class: Class 8: Corrosive Substances.

Packing Group: III

Packing Instruction: P001, IBC03, LP01

Class 8 Corrosive Substances shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances where the Toxic Substances are cyanides and the Corrosives are acids), 7 (Radioactive Substances), Foodstuffs and foodstuff empties. They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases), 2.2 (Non-Flammable, Non-Toxic Gases), 2.3 (Poisonous Gases), 3 (Flammable liquids), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 6 (Toxic Substances except where the Toxic Substances are cyanides and the Corrosives are acids) and 9 (Miscellaneous Dangerous Goods).

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

AICS

Australian Inventory of Chemical Substances

SWA

Safe Work Australia, formerly ASCC and NOHSC

CAS number

Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

IARC International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

R-Phrase Risk Phrase

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous

Chemicals - Code of Practice" (Feb 2016) Copyright © Kilford & Kilford Pty Ltd, June, 2023. http://www.kilford.com.au/ Phone (02)8321 8866

Issued by: Atech Products Pty Ltd Phone: +61 3 9028 4265