Page: 1 of 6

This version issued: June, 2022

Section 1 - Identification of The Material and Supplier

ATECH PRODUCTS PTY LTD Phone: 1300 283 249
PO BOX 3119 BURNELY NORTH

VIC 3121 AUSTRALIA

Chemical nature: Water based epoxy resin with pigments and extenders.

Trade Name: MIGHTYPRIME™ PART A

Other Names: This is part A of a two part system.

Product Use: Water based epoxy sealer - two part system.

Creation Date: May, 2016
This version issued: June, 2022

Poisons Information Centre: Phone 13 11 26 from anywhere in Australia

EMERGENCY RESPONSE NUMBER

Organisation: CHEMWATCH EMERGENCY RESPONSE

Emergency response number(s): Australia: +61 3 9573 3188

New Zealand: +64 800 700 112

Other emergency response number(s): +61 1800 951 288

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xi, Irritating. N, Dangerous to the environment. Hazardous according to the criteria of SWA.

Not subject to the ADG Code when transported in Australia by Road or Rail in packages 500kg(L) or less; or IBCs (refer to SP AU01). However if transported by Air or Sea, this provision does not apply. Then the product is classed as Dangerous (Class 9 Environmentally Hazardous) by IATA and IMDG/IMSBC respectively. See details below and in Section 14 of this SDS.

SUSMP Classification: None allocated.

ADG Classification: Class 9: Miscellaneous Dangerous Goods.

UN Number: 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.





Phone: 1300 283 249

GHS Signal word: WARNING

Skin Corrosion /Irritation Category 2

Skin Sensitisation Category 1

Serious eye damage/eye irritation Category 2B

Hazardous to aquatic environment Short term/Chronic Category 2

HAZARD STATEMENT:

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H320: Causes eye irritation.

H411: Toxic to aquatic life with long lasting effects.

PREVENTION

P102: Keep out of reach of children.

P261: Avoid breathing fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

SAFETY DATA SHEET

Issued by: Atech Products Pty Ltd

Page: 2 of 6

This version issued: June, 2022

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P362: Take off contaminated clothing and wash before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313: If skin irritation or rash occurs: Get medical advice.

P337+P313: If eve irritation persists: Get medical advice.

P391: Collect spillage.

P370+P378: Not combustible. Use extinguishing media suited to burning materials. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used.

STORAGE

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: White viscous liquid.

Odour: Characteristic odour.

Major Health Hazards: irritating to eyes and skin, possible skin sensitiser.

Section 3 - Corr position/Inforration on Ingredients						
Ingredients	CAS No	Conc,%	TWA (mg/m³)	STEL (mg/m³)		
Epoxy resin	25068-38-6	30-60	not set	not set		
Non hazardous pigments and extenders	secret	10-30	not set	not set		
Other non hazardous ingredients	secret	<5	not set	not set		
Water	7732-18-5	to 100	not set	not set		

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

Skin Contact: Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Page: 3 of 6

This version issued: June, 2022

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is little risk of an explosion from this product if commercial quantities are involved in a fire

This product is likely to decompose only after heating to dryness, followed by further strong heating.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Not combustible. Use extinguishing media suited to burning materials. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is little danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flash point: Does not burn.

Upper Flammability Limit: Does not burn.

Lower Flammability Limit: Does not burn.

Autoignition temperature: Not applicable - does not burn.

Flammability Class: Does not burn.

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Because of the environmentally hazardous nature of this product, special care should be taken to restrict release to waterways or drains. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Although this is classed as a Dangerous Good, you may not need a license to store it. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits TWA (mg/m³) STEL (mg/m³)

Exposure limits have not been established by SWA for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Page: 4 of 6

This version issued: June, 2022

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: If you believe you may have a sensitisation to this product or any of its declared ingredients, you should prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour: White viscous liquid. Characteristic odour.

Boiling Point: Approximately 100°C at 100kPa.

Freezing/Melting Point: No specific data. Liquid at normal temperatures.

Volatiles: Water component.

Vapour Pressure: 2.37 kPa at 20°C (water vapour pressure).

Vapour Density: As for water. **Specific Gravity:** 1.0-1.5 Water Solubility: Dispersible. pH: No data. Volatility: No data **Odour Threshold:** No data. **Evaporation Rate:** As for water. **Coeff Oil/water Distribution:** No data

Autoignition temp: Not applicable - does not burn.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: Keep containers tightly closed.

Incompatibilities: acids, bases, oxidising agents, amines, polymerisation initiators.

Fire Decomposition: This product is likely to decompose only after heating to dryness, followed by further strong heating. Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form hydrogen chloride gas, other compounds of chlorine. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product may undergo polymerisation in the presence of certain chemical reagents. See Incompatibilities above. Polymerisation is often accompanied by liberation of heat, and may lead to a dangerous or explosive situation. If the product is seen to be heating up, treat as a fire incident.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Epoxy Resin is classed by SWA as a potential sensitiser by skin contact.

Classification of Hazardous Ingredients

Ingredient Risk Phrases

Epoxy Resin Conc>=5%: Xi; R36/38; R43

- Eye irritation category 2
- Skin irritation category 2
- Skin sensitisation category 1
- Hazardous to the aquatic environment (chronic) category 2

SAFETY DATA SHEET

Issued by: Atech Products Pty Ltd Phone: **1300 283 249**

Page: 5 of 6

This version issued: June, 2022

Potential Health Effects

Persons sensitised to Epoxy resins should avoid contact with this product.

Inhalation:

Short Term Exposure: Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Classified as a potential sensitiser by skin contact. Exposure to a skin sensitiser, once sensitisation has occurred, may manifest itself as skin rash or inflammation, and in some individuals this reaction can be severe. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP. **IARC:** No significant ingredient is classified as carcinogenic by IARC.

Section 12 - Ecological Information

Toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment. This product is not readily biodegradable. However, likely to degrade slowly in the soil or water and not cause long term problems.

Section 13 - Disposal Considerations

Disposal: Containers should be emptied as completely as practical before disposal. If possible, recycle product and containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site.

Section 14 - Transport Information

Not subject to the ADG Code when transported by Road or Rail in Australia, in packages 500kg(L) or less; or IBCs, but classed as Dangerous by IATA and IMDG/IMSBC when carried by Air or Sea transport (see details below).

UN Number: 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazchem Code: •3Z

Special Provisions: 179, 274, 331, 335, AU01

Limited quantities: ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

Dangerous Goods Class: Class 9: Miscellaneous Dangerous Goods.

Packing Group: III

Packing Instruction: P001, IBC03, LP01

Class 9 Miscellaneous Dangerous Goods shall not be loaded in the same vehicle or packed in the same freight container with Dangerous Goods of Class 1 (Explosives).

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Issued by: Atech Products Pty Ltd Phone: **1300 283 249**

age: 6 of 6

This version issued: June, 2022

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

AICS
Australian Inventory of Chemical Substances
SWA
Safe Work Australia, formerly ASCC and NOHSC
CAS number
Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

IARC International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

R-Phrase Risk Phrase

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous

Chemicals - Code of Practice" (December 2011) Copyright © Kilford & Kilford Pty Ltd, June, 2023. http://www.kilford.com.au/ Phone (02)9251 4532

Page: 1 of 6

This version issued: June, 2022

Phone: 1300 283 249

Section 1 - Identification of The Material and Supplier

ATECH PRODUCTS PTY LTD
PO BOX 3119 BURNELY NORTH

VIC 3121 AUSTRALIA

Chemical nature: Water based blend of amines and other ingredients.

Trade Name: MIGHTYPRIME™ PART B
Other Names: This is Part B of a two part system.

Product Use: Water based epoxy sealer - two part system.

Creation Date: May, 2016

This version issued: June, 2022 and is valid for 5 years from this date.

Poisons Information Centre: Phone 13 11 26 from anywhere in Australia

EMERGENCY RESPONSE NUMBER

Organisation: CHEMWATCH EMERGENCY RESPONSE

Emergency response number(s): Australia: +61 3 9573 3188

New Zealand: +64 800 700 112

Other emergency response number(s): +61 1800 951 288

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: N, Dangerous to the environment. C, Corrosive. Hazardous according to the criteria of SWA.

Not a Dangerous Good according to Australian Dangerous Goods (ADG) Code, IATA or IMDG/IMSBC criteria.

SUSMP Classification: None allocated.

ADG Classification: None allocated. Not a Dangerous Good according to Australian Dangerous Goods (ADG)

Code, IATA or IMDG/IMSBC criteria.

UN Number: None allocated





GHS Signal word: DANGER

Skin Corrosion /Irritation Category 1

Skin Sensitisation Category 1

Hazardous to aquatic environment Short term/Acute Category 2

HAZARD STATEMENT:

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H401: Toxic to aquatic life.

PREVENTION

P102: Keep out of reach of children.

P260: Do not breathe fumes, mists, vapours or spray.

P261: Avoid breathing fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P310: Immediately call a POISON CENTRE or doctor/physician.

SAFETY DATA SHEET

Issued by: Atech Products Pty Ltd Phone: 1300 283 249

Page: 2 of 6

This version issued: June, 2022

Phone: 1300 283 249

P363: Wash contaminated clothing before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water. P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313: If skin irritation or rash occurs: Get medical advice.

P370+P378: Not combustible. Use extinguishing media suited to burning materials.

STORAGE

P405: Store locked up.

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: Light grey, viscous liquid.

Odour: Characteristic amine odour.

Major Health Hazards: causes burns, possible skin sensitiser.

Section 3 - C mposition/Inforr ation on Ingredients					
Ingredients	CAS No	Conc,%	TWA (mg/m³)	STEL (mg/m ³)	
Polyamine polymer	68410-23-1	10-20	not set	not set	
Triethylenetetramine	112-24-3	3-5	not set	not set	
Other non hazardous ingredients	various	<10	not set	not set	
Water	7732-18-5	to 100	not set	not set	

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

Skin Contact: Flush contaminated area with lukewarm, gently flowing water for at least 20-30 minutes, by the clock. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this MSDS and take their advice). Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts). If irritation persists, repeat flushing. Seek medical attention.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 20-30 minutes, by the clock, while holding the eyelid(s) open. Neutral saline solution may be used as soon as it is available. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this MSDS and take their advice). Take care not to rinse contaminated water into the unaffected eye or onto face. If irritation persists, repeat flushing. Call a Poisons Information Centre or a doctor urgently. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting; rinse mouth thoroughly with water and contact a Poisons Information Centre. Urgent hospital treatment is likely to be needed. Give activated charcoal if instructed.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

Page: 3 of 6

This version issued: June, 2022

This product is likely to decompose only after heating to dryness, followed by further strong heating.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Not combustible. Use extinguishing media suited to burning materials. **Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade.

Flash point: No data.

Upper Flammability Limit: No data.

Lower Flammability Limit: No data.

Autoignition temperature: No data.

Flammability Class: No data.

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective chemically resistant clothing including eye/face protection, gauntlets and self contained breathing apparatus. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include no specific manufacturer recommendations. Use impermeable gloves with care. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Store packages of this product in a cool place. Make sure that containers of this product are kept tightly closed. Keep containers dry and away from water. Keep containers of this product in a well ventilated area. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Some liquid preparations settle or separate on standing and may require stirring before use. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits TWA (mg/m³) STEL (mg/m³)

Exposure limits have not been established by SWA for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Your eyes must be completely protected from this product by splash resistant goggles with face shield. All surrounding skin areas must be covered. Emergency eye wash facilities must also be available in an area close to where this product is being used.

Skin Protection: Because of the dangerous nature of this product, make sure that all skin areas are completely covered by impermeable gloves, overalls, hair covering, apron and face shield. See below for suitable material types.

Protective Material Types: There is no data that enables us to recommend any type except that it should be impermeable.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

SAFETY DATA SHEET

Page: 4 of 6

This version issued: June, 2022

Phone: 1300 283 249

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour: Light grey, viscous liquid.
Odour: Characteristic amine odour.

Boiling Point: Approximately 100°C at 100kPa.

Freezing/Melting Point: Approximately 0°C. **Volatiles:** Water component.

Vapour Pressure: 2.37 kPa at 20°C (water vapour pressure).

Vapour Density: As for water. Specific Gravity: 1.0-1.5

Water Solubility: Completely soluble in water.

pH: No data.

Volatility: No data.

Odour Threshold: No data.

Evaporation Rate: As for water.

Coeff Oil/water Distribution: No data

Autoignition temp: No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated.

Incompatibilities: strong acids, oxidising agents.

Fire Decomposition: This product is likely to decompose only after heating to dryness, followed by further strong heating. Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas in reducing atmospheres. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Triethylenetetramine is classed by SWA as a potential sensitiser by skin contact.

Classification of Hazardous Ingredients

Ingredient Risk Phrases

Triethylenetetramine >=1%Conc<5%: Xi; R43

- Acute toxicity category 4
- Skin corrosion category 1B
- Skin sensitisation category 1
- Hazardous to the aquatic environment (chronic) category 3

Potential Health Effects

Persons sensitised to Triethylenetetramine should avoid contact with this product.

Inhalation:

Short Term Exposure: Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort. If liquid enters nasal passages, it will cause pain and burn nasal membranes. Patients with inhalation burns may develop acute pulmonary oedema.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Classified as a potential sensitiser by skin contact. Exposure to a skin sensitiser, once sensitisation has occurred, may manifest itself as skin rash or inflammation, and in some individuals this reaction can

SAFETY DATA SHEET

Issued by: Atech Products Pty Ltd

Page: 5 of 6

This version issued: June, 2022

Phone: 1300 283 249

be severe. In addition product is corrosive to the skin. Capable of causing moderate to severe burns with ulceration. Can penetrate to deeper layers of skin, resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure. Burns may not be immediately painful; the onset of pain may be minutes to hours.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is corrosive to eyes. It will cause severe pain, and corrosion of the eye and surrounding facial tissues. Unless exposure is quickly treated, permanent blindness and facial scarring is likely.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product is corrosive to the gastrointestinal tract. Capable of causing moderate to severe burns with ulceration. Can penetrate to deeper layers of skin, resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP. **IARC:** No significant ingredient is classified as carcinogenic by IARC.

Section 12 - Ecological Information

This product is toxic to aquatic organisms. This product is believed to be biodegradable. It is unlikely to accumulate in the soil or water or cause long term problems.

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable in-house, consider controlled incineration, or contact a specialist waste disposal company.

Section 14 - Transport Information

UN Number: This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

AICS Australian Inventory of Chemical Substances
SWA Safe Work Australia, formerly ASCC and NOHSC
CAS number Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

IARC International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

R-Phrase Risk Phrase

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS

SAFETY DATA SHEET

Issued by: Atech Products Pty Ltd

Phone: 1300 283 249

This version issued: June, 2022 OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011)

Copyright © Kilford & Kilford Pty Ltd, June, 2023.

http://www.kilford.com.au/ Phone (02)9251 4532